

4645

Wireless local alarm acknowledge unit



Features

- › Eliminates unnecessary alarms in the system and to the fire brigade.
- › Suitable for apartments or similar locations.
- › Installed together with a smoke detector and a sounder base.
- › If the detector goes into alarm the sounder is activated and the LED is lit. The user pushes the button within 30 seconds (configurable) and then gets 3 minutes (configurable) to ventilate the smoke from the room.
- › Minimum 170 m transmission range (open air)
- › 6 years battery life
- › High flexibility: Up to 4 base stations on each COM loop and up to 16 wireless units on each base station

General

- › Two batteries included

Order number

- › 4645 - Wireless local alarm acknowledge unit

Related products

- › 4400 - Analog multi detector
- › 4400I - Analog multi detector with isolator
- › 4401 - Analog photoelectric smoke detector
- › 4401I - Analog smoke detector with isolator
- › 4611 - Wireless photoelectric smoke detector
- › 4479 - Addressable sounder base
- › 4436 - Key
- › 4612 - Battery (spare part)
- › 4613 - Wireless sniffer (USB device with antenna)
- › 4620 - Addressable base station for wireless units



250 g,
2 batteries included



135 x 135 x 36 mm



3V Lithium/1600 mAh



868 MHz



-10 TO +55 °C



Red LED



<95%

